



pathfinder systems

Epoxymix Anti-Slip Specifications

Template/Tape Application



Clean surface for application



Layout Epoxymix templates as desired

OR



Apply masking tape either side of desired strip



Apply Epoxymix Antislip into desired cavity until slight overflow



Use a scraper to flatten and remove excess epoxy

Channels



Clean channel for application



Apply Epoxymix Antislip into desired channel until slight overflow



Use a scraper to flatten and remove excess epoxy

Colour

Black

Yellow

White

Terracotta

Charcoal

Sandstone

Sets in just
4 Hours!

400ml

VeryStrongBond:SurfaceEpoxy
ISO 9001:2000 **ANTISLIP**

EPOXYMIX™

Applications:

- Steps
- Ramps
- Walkways
- Public building entries
- Suitable for wet areas in domestic or commercial areas

Features:

- Good anti slip properties
- Rapid set
- No mixing
- Easy to apply
- Very good adhesion to most substrates; Concrete, ceramic, metal, wood.
- Can be applied to damp surfaces

Styrene Free - Odour friendly

Unit 3, 96, Judd Road
Prestons NSW 2170
1300 362 775

Epoxymix is a brand of Pathfinder Systems Australia Pty Ltd.

Specifications

Product name: Epoxymix Anti-Slip

Product code: EVSB-AS

Material: Pure epoxy resin with silica quartz

Packaging Size: 400ml (side by side 3:1 cartridge)

Finish/colours: Textured surface - available in 6 colours, see chart below.

Application width: Stair treads require a min 50mm wide strip as per AS 1428.4.1.2009. Slippery surface application as per surface design templates supplied.

Storage: do not expose sunlight, store in dry area between 5C -25C

Slip Test ratings: R11 / P5-V slip rating (CSIRO reports available)

Curing times:

30c-40c = 2hrs

20c-30 = 4 hrs

15c = 8 hrs

Direction:

- Screw fix pre mixing nozzle to cartridge.
- Discard initial amount of material until the two parts mix and become a solid colour.(approx. 100mm strip)