



TECHNICAL DATA SHEET

Great Epoxies, Great Price...

Product Name:	EPOXYMIX VeryStrongBond surface epoxy
Product Code:	VSB-SE-Anti-Slip 400ml (VeryStrongBond-surface epoxy- Anti-Slip 400ml)
Manufacturer:	Unlicensed for; Pathfinder Systems Australia Unit 3 95 Jemma Road. Prestons NSW
Telephone:	Ph: 02 96086019
Website:	www.epoxymix.com.au
Advantages:	May be used on damp surfaces
	May be used on concrete, ceramic, brick, stone and timber
	Easy to use in a wide range of temperatures.
	High strength adhesive and one of the strongest in the industry
	Very good anti slip properties
	Fast cure with negligible shrinkage.

Application procedure	
Step 1	Make sure surface is clean of any contaminants and block of area to stop public from entering work area.
Step 2	If installation is over glazed tiles or surfaces that have been pre-coated with sealers etc; mechanically etch / or sand the surface where you are applying the Epoxymix Anti-Slip to insure a better bond.
Step 3	Apply the material to areas you have prepared to a thickness/design you require. Normally 1-2mm thick is sufficient. It is best to use templates as supplied by distributor but not essential.
Step 4	When your application is finished, keep foot traffic off for required drying time, see below for drying times

Gel and open to foot traffic times		
Application Temperature(°C)		Open to public Time(hrs)
35		2.5
25		4
15		10
5		12

Order information

Product	VSB-Epoxymix Anti-Slip	Shelf life:	24 months
Size	400ml	Case qty:	20
Pneumatic Dispensing Tool:		Mix ratio:	3:1
		Mix color:	Blk, Yell, White, Charcoal, Stone, Red Terra
		Storage :	below 20°C